

# HOUGHTON CHEMICAL CORPORATION

52 Cambridge Street, Allston (Boston), MA 02134  
Phone: (800) 777-2466 Fax: (617) 254-2713  
www.houghton.com



## PAH|NOL® ISO-PREME GAS LINE A/F Product Data Sheet

### 2-Propanol-based Gas Line Treatment

PAH|NOL® ISO-PREME Gas Line Antifreeze removes dissolves water in gas lines and tanks, allowing it to flow through fuel pumps and engines without fouling.

For health and safety information for this product, contact Houghton for a Material Safety Data Sheet (MSDS).

## PAH|NOL® ISO-PREME GAS LINE A/F Typical Properties

Properties	Values
2-Propanol	99-100%
Appearance	Form: liquid      Color: colorless
Specific Gravity (15/15°C 60/60°F)	0.785 @ 25.0°C (77.0°F)

Use Recommendation: Add one bottle of PAH|NOL® ISO-PREME Gas Line Antifreeze to the gas tank through the fill line prior to filling the gas tank.

Typical properties, not to be construed as specifications. As use conditions are not within its control, Houghton does not guarantee results from use of the information or products herein; and gives no warranty, express or implied.

**NOTICE:** No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.