Houghton Chemical Corporation

Safety Data Sheet



SAFE-T-THERM® GRAS Biobased

			Section 1 - Identifica	tion				
Manufacturer Address Hou		Houg	ghton Chemical Corporation					
		52 Ca	52 Cambridge Street, Allston, MA 02134					
		1-617-254-1010 or 1-800-777-2466						
Emergency Telephone CH			MTREC: 1-800-424-9300					
Chemical Name & Synonyms Antif			eeze/Inhibited Propylene Glyco	ol .				
Chemical Family			lene Glycol Mixture					
Recommended U	se		Transfer Fluid					
Restrictions on U	se		on to 50% is generally recomm		I condition.			
11 101 10			ection 2 – Hazard(s) Iden	itification				
Hazard Classifica	ition		pplicable					
Signal Word			pplicable					
			nile this material is not considered hazardous by the OSHA Hazard Communication					
Hazard Statemen	it		lard (29 CFR 1910.1200), this		ormation critical to the			
D:			nandling and proper use of this	product.				
Pictogram Descri	ption		pplicable					
			container tightly closed. Keep					
Precautionary Sta	atement	smoking, drinking or eating around product. Wear protective gloves, eye and face						
,		equipment. Store in a cool, dry and well-ventilated location. Avoid release to the						
Any other Hazard	I not otherwise		environment.					
classified	THOU OTHER WISE	Not A	pplicable					
	Section	3 – C	Composition and Informa	ation on Ingredients				
Chemical Name			common name and synonyms	CAS#	% by weight			
Propylene Glycol			,2 - Propanediol	57-55-6	96%			
Water			i/A	7732-18-5	2%			
Inhibitors & Dye		N	I/A	Proprietary	2%			
j				. ,				
			Section 4 - First aid Me	asures	·			
			Symptoms of Exposur					
Acute	Irritation of affe	cted ar	ea					
Delayed	Irritation							
Inhalation	Vapors and mis	sts expe	ected to be slightly irritating to u	upper respiratory tract.				
Skin	Irritation may re	esult						
Eye Contact	Irritation may c	ause tra	ansitory stinging and tearing.					
Ingestion			ested. Ingestion of larger amou		stinal upset and			
ingestion	possible tempo	rary ce	ntral nervous system depression					
			First Aid Instructions					
Inhalation								
Skin	Wash skin with soap and water. Remove any contaminated clothing. Seek medical attention if							
irritations develops or persists.								
Eye Contact Flush with water for at least 20 minutes. Seek medical attention if irritations develops or persists.								
Ingestion								
Other	Not Applicable							
		Se	ection 5 – Fire Fighting N					
Suitable Extinguishing Material			Water, water fog, water spray, alcohol foam, dry chemical or carbon dioxide					
Unsuitable Extinguishing Material			No Data Available					
Hazards from Combustion		Smoke may contain the original material in addition to but not limited to: Carbon Monoxide, Carbon Dioxide.						
Special Protective Equipment for			Wear self-contained breathing apparatus and protective suit. Evacuate					
Firefighters			personnel to safe areas and keep upwind of fire.					
-			Page 1 of 4					

Use of personal precautions Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Usage of safety glasses or googles is recommended. Chemical resistant gloves, chemical resistant apron, boots, and full suit will be necessary depending on the extent of clean up task. If ventilation do not control airborne concentration then respiratory protection equipment that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements should be used. Methods and materials used for containment Cleanup procedures Do not flush to sewer. Comply with all federal, state, and local regulations. Section 7 - Handling and Storage Protect container from physical damage. Wear appropriate personal protection equipment. Do not expose containers to open flame,		Section 6 -	Accidental Release Measures				
appropriate personal protective equipment. Usage of safety glasses or googles is recommended. Chemical resistant gloves, chemical resistant apron, boots, and full suit with encessary depending on the extent of clean up task. If wentilation do not control airborne concentration then respiratory protection equipment that meets OSHA's 29 CFR 1910.134 and ANSI 288.2 requirements should be used. Cleanup procedures Section 7 - Handling and Storage Protect container from physical damage. Wear appropriate personal protection equipment. Do not expose containers to open flame, excessive heat, or direct sunlight. Use local exhaust over processing area. Do not eat, drink or smoke around products. Section 8 - Exposure container area away from sources of heat, moisture and incompatible materials. Observe all warnings and precautions listed for the product. Keep container closed to prevent contamination. Section 8 - Exposure Controls/Personal Protection OSHA Permissible Exposure Limits (PELs) American Conference of Governmental Industrial Highenists (ACGH) Threshold Limit Values Other Exposure Limits Engineering Control Section 9 - Physical and Chemical and Chemical and Chemical repositions. AlHA WEEL is 10 mg/m3 for total vapor and aerosol. Use mechanical (general) ventilation to control airborne levels below exposure guidelines. Appearance (physical state, color, etc.) Liquid, Clear, Green Golder Harmability or explosive limits Not Explosive; LOWER: 2.6% (v) UPPER: 12.5% (v) Wapor density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1) PH 9.0 - 10.5 Relative density (air = 1)							
Usage of safety glasses or googles is recommended. Chemical resistant apron, boots, and full suit will be necessary depending on the extent of clean up task. If ventilation on contentation then respiratory protection equipment that meets CSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements should be used. Methods and materials used for containment	Use of personal precautions						
Requirements should be used.			Usage of safety glasses or googles is recommended. Chemical resistant gloves, chemical resistant apron, boots, and full suit will be necessary depending on the extent of clean up task. If ventilation does not control airborne concentration then respiratory protection				
And place in chemical waste container.			requirements should be used.				
regulations. regulations. regulations. regulations. regulations. regulations. regulations. regulations. regulations. regulations. respectively. respective	Methods and materials used for co	ntainment	and place in chemical waste container.				
Protect container from physical damage. Wear appropriate personal protection equipment. Do not expose containers to open flame, excessive heat, or direct sunlight. Use local exhaust over processing area. Do not eat, drink or smoke around products. Precautions for safe handling	Cleanup procedures						
Protect container from physical damage. Wear appropriate personal protection equipment. Do not expose containers to open flame, excessive heat, or direct sunlight. Use local exhaust over processing area. Do not eat, drink or smoke around products. Store in a cool, dry and ventilated area away from sources of heat, moisture and incompatible materials. Observe all warnings and precautions listed for the product. Keep container closed to prevent contamination. Section 8 – Exposure Controls/Personal Protection OSHA Permissible Exposure Limits (PELs) American Conference of Governmental industrial Hygienists (ACGIH) Threshold Limit Values Other Exposure Limits Engineering Control Use mechanical (general) ventilation to control airborne levels below exposure guidelines. Wear protective safety glasses or goggles, gloves, apron, vapor respirator. Section 9 – Physical and Chemical and Chemical Properties Appearance (physical state, color, etc.) Upper/lower flammability or explosive limits Odor Sight to no odor Sight to no odor Sight to no odor Sight to no odor Sight in on odor Sight in midtle properties Not Applicable Vapor density (air = 1) 9.0 - 10.5 Relative density 1.055 - 1.065 Freezing point (as 50%) 2.2°F / -31°C Solubility(ies) Miscible in water Initial boiling point and boiling range Flammability (solid, gas) Not Flammabile Vapor in the product. Keep container closed to prevent contamination. Product is stable under typical use temperatures. Not Explosive LOWER: 2.6% (v) UPPER: 12.5% (v) Solubility(ies) Not Flammabile Not Applicable 1.1°F / 155°C Flammability (solid, gas) Not Flammabile Vapor in the product. Keep container closed to prevent contamination. Product is stable under typical use temperatures. Product is stable under typical use temperatures. Avoid contact with oxidizing materials and strong acids.		Section					
Precautions for safe handling Precautions for safe handling Precautions for safe handling Recommendations on the conditions for safe storage, Storage/handling incompatibilities. Store in a cool, dry and ventilated area away from sources of heat, moisture and incompatible materials, Observe all warnings and precautions listed for the product. Keep container closed to prevent contamination. Section 8 – Exposure Controls/Personal Protection Section 8 – Exposure Controls/Personal Protection Section 8 – Exposure Controls/Personal Protection Not Applicable Not Explosive, LOWER: 2.6% (v) UPPER: 12.5% (v) Slight to no odor Vapor pressure 133 Pa / 0.1 mmHg Not Applicable Not Explosive, LOWER: 2.6% (v) UPPER: 12.5% (v) Slight to no odor Vapor pressure 133 Pa / 0.1 mmHg Not Applicable Not Explosive, LOWER: 2.6% (v) UPPER: 12.5% (v) Section 10 Section 3 Not Applicable Not Explosive applicab		Section					
Store in a cool, dry and ventilated area away from sources of heat, moisture and incompatible materials. Observe all warnings and precautions listed for the product. Keep container closed to prevent contamination. Section 8 - Exposure Controls/Personal Protection	5 (()						
moisture and incompatible materials. Observe all warnings and precautions listed for the product. Keep container closed to prevent contamination. Section 8 – Exposure Controls/Personal Protection OSHA Permissible Exposure Limits (PELs) American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values Other Exposure Limits Other Exposure Limits Individual Protection Measures Section 9 – Physical and Chemical and Chemical Properties Individual Protection Measures Section 9 – Physical and Chemical and Chemical Properties Appearance (physical state, color, etc.) Upper/lower flammability or explosive limits Odor Threshold Vapor pressure Odor threshold Vapor density (air = 1) PH 9.0 - 10.5 Relative density Freezing point (as 50%) Freezing point (as 50%) Freezing point and boiling range Flash point Evaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Not Applicable Not Applicable	Precautions for safe handling						
Section 8 – Exposure Controls/Personal Protection OSHA Permissible Exposure Limits (PELs) American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values Other Exposure Limits Engineering Control Individual Protection Measures Section 9 – Physical and Chemical and Chemical Properties Appearance (physical state, color, etc.) Upper/lower flammability or explosive limits Not Applicable Appearance (physical state, color, etc.) Upper/lower flammability or explosive limits Not Explosive; LOWER: 2.6% (v) UPPER: 12.5% (v) Odor Slight to no odor Vapor pressure Odor threshold Not Applicable Vapor density (air = 1) PH 9.0 - 10.5 Relative density 1.055 - 1.065 Freezing point (as 50%) -22°F / -31°C Solubility(les) Initial boiling point and boiling range 311°F / 155°C Flash point Evaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Not Explosive at 60°F Section 9 – Physical and Chemical and Chemical Properties Not Explosive; LOWER: 2.6% (v) UPPER: 12.5% (v) Were protective safety glasses or goggles, gloves, apron, vapor respirator. Wear protective safety glasses or goggles, gloves, apron, vapor respirator. Wear protective safety glasses or goggles, gloves, apron, vapor respirator. Wear protective safety glasses or goggles, gloves, apron, vapor respirator. Wear protective safety glasses or goggles, gloves, apron, vapor respirator. Vapor protective safety glasses or goggles, gloves, apron, vapor respirator. Not Applicable 1.02er, Green Not Applicable 1.03 Pa / 0.1 mmHg Not Applicable 1.055 - 1.065 Freezing point (as 50%) 2.2°F / 31°C Solubility(les) Not Flammabile Not Flammability (solid, gas) Not Flammabile Not Applicable 1.055 - 1.065 Not Applicable 1.056 - 1.056 Not Applicable 1.057 - 7.07°C 1.057 -			moisture and incompatible materials. Observe all warnings and precautions listed for the product. Keep container closed to prevent				
OSHA Permissible Exposure Limits (PELs) Not Applicable							
American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values Other Exposure Limits Confirm Exposure Limits Confirm Control Condition to Avoid Conditions to Avoid Condit							
Use mechanical (general) ventilation to control airborne levels below exposure guidelines. Wear protective safety glasses or goggles, gloves, apron, vapor respirator.	American Conference of Governm Industrial Hygienists (ACGIH) Thre	ental					
exposure guidelines. Individual Protection Measures Section 9 - Physical and Chemical and Chemical Properties Appearance (physical state, color, etc.) Liquid, Clear, Green Upper/lower flammability or explosive limits Not Explosive; LOWER: 2.6% (v) UPPER: 12.5% (v) Odor Slight to no odor Vapor pressure Odor threshold Not Applicable Vapor density (air = 1) PH 9.0 - 10.5 Relative density Freezing point (as 50%) Solubility(ies) Miscible in water Initial boiling point and boiling range 311°F / 155°C Flash point Evaporation rate (Butyl Acetate = 1) Partition coefficient: n-octanol/water Auto-ignition temperature Auto-ignition temperature; and Viscosity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Conditions to Avoid Heat, flames, ignition sources and incompatibles.	Other Exposure Limits						
Respirator Res	Engineering Control		exposure guidelines.				
Appearance (physical state, color, etc.) Upper/lower flammability or explosive limits Not Explosive; LOWER: 2.6% (v) UPPER: 12.5% (v) Slight to no odor Vapor pressure 133 Pa / 0.1 mmHg Odor threshold Not Applicable Vapor density (air = 1) PH 9.0 - 10.5 Relative density 1.055 - 1.065 Freezing point (as 50%) Solubility(ies) Initial boiling point and boiling range Initial boiling point and boiling range Vaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature; and Viscosity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Chemical Stability Reactions to Avoid Heat, flames, ignition sources and incompatibles.	Individual Protection Measures						
Appearance (physical state, color, etc.) Upper/lower flammability or explosive limits Not Explosive; LOWER: 2.6% (v) UPPER: 12.5% (v) Slight to no odor Vapor pressure 133 Pa / 0.1 mmHg Odor threshold Not Applicable Vapor density (air = 1) PH 9.0 - 10.5 Relative density 1.055 - 1.065 Freezing point (as 50%) Solubility(ies) Initial boiling point and boiling range Initial boiling point and boiling range Vaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature; and Viscosity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Chemical Stability Reactions to Avoid Heat, flames, ignition sources and incompatibles.	Section 9	- Physical	and Chemical and Chemical Properties				
Odor Slight to no odor Vapor pressure 133 Pa / 0.1 mmHg Odor threshold Not Applicable Vapor density (air = 1) 2.1 pH 9.0 - 10.5 Relative density 1.055 - 1.065 Freezing point (as 50%) -22°F / -31°C Solubility(ies) Miscible in water Initial boiling point and boiling range 311°F / 155°C Flash point 225°F / 107°C Evaporation rate (Butyl Acetate = 1) <1 Flammability (solid, gas) Not Flammable Partition coefficient: n-octanol/water No Data Available Auto-ignition temperature > 700°F / > 370°C Decomposition temperature; and Not Applicable Viscosity -75 cps at 60°F Section 10 - Stability and Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid Heat, flames, ignition sources and incompatibles.			•				
Vapor pressure Odor threshold Not Applicable Vapor density (air = 1) PH 9.0 - 10.5 Relative density 1.055 - 1.065 Freezing point (as 50%) -22°F / -31°C Solubility(ies) Miscible in water Initial boiling point and boiling range Initial boiling point and boiling range Flash point 225°F / 107°C Evaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Not Flammable Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature; and Viscosity Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable Section 10 - Stability and Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.	Upper/lower flammability or explos	ive limits					
Odor threshold Not Applicable Vapor density (air = 1) 2.1 pH 9.0 - 10.5 Relative density 1.055 - 1.065 Freezing point (as 50%) -22°F / -31°C Solubility(ies) Miscible in water Initial boiling point and boiling range 311°F / 155°C Flash point 225°F / 107°C Evaporation rate (Butyl Acetate = 1) <1							
Vapor density (air = 1) pH 9.0 - 10.5 Relative density 1.055 - 1.065 Freezing point (as 50%) -22°F / -31°C Solubility(ies) Miscible in water Initial boiling point and boiling range 311°F / 155°C Flash point 225°F / 107°C Evaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Partition coefficient: n-octanol/water No Data Available Auto-ignition temperature Decomposition temperature; and Viscosity -75 cps at 60°F Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.							
PH 9.0 - 10.5 Relative density 1.055 - 1.065 Freezing point (as 50%) -22°F / -31°C Solubility(ies) Miscible in water Initial boiling point and boiling range 311°F / 155°C Flash point 225°F / 107°C Evaporation rate (Butyl Acetate = 1) <1 Flammability (solid, gas) Not Flammable Partition coefficient: n-octanol/water No Data Available Auto-ignition temperature > 700°F / > 370°C Decomposition temperature; and Not Applicable Viscosity -75 cps at 60°F Section 10 - Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid Heat, flames, ignition sources and incompatibles.			• • • • • • • • • • • • • • • • • • • •				
Relative density Freezing point (as 50%) Solubility(ies) Miscible in water Initial boiling point and boiling range Stable in water Initial boiling point and boiling range Initial boiling point and boiling range Stable in water 311°F / 155°C Flash point Stable in water 225°F / 107°C Evaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Not Flammable Partition coefficient: n-octanol/water No Data Available Auto-ignition temperature Not Applicable Viscosity Not Applicable Viscosity Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.							
Freezing point (as 50%) Solubility(ies) Miscible in water Initial boiling point and boiling range S11°F / 155°C Flash point 225°F / 107°C Evaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Partition coefficient: n-octanol/water No Data Available Auto-ignition temperature Auto-ignition temperature; and Viscosity Not Applicable Viscosity Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.	•						
Solubility(ies) Initial boiling point and boiling range Initial boiling point and saling poi							
Initial boiling point and boiling range Flash point 225°F / 107°C Evaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Partition coefficient: n-octanol/water No Data Available Auto-ignition temperature Auto-ignition temperature; and Viscosity Not Applicable Viscosity Not Applicable Viscosity Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.	01 \						
Flash point Evaporation rate (Butyl Acetate = 1) Flammability (solid, gas) Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature; and Viscosity Not Applicable -75 cps at 60°F Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.							
Evaporation rate (Butyl Acetate = 1) <1 Flammability (solid, gas) Not Flammable Partition coefficient: n-octanol/water No Data Available Auto-ignition temperature > 700°F / > 370°C Decomposition temperature; and Not Applicable Viscosity ~75 cps at 60°F Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.		je					
Flammability (solid, gas) Partition coefficient: n-octanol/water Auto-ignition temperature Auto-ignition temperature; and Viscosity Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Not Flammable No Data Available > 700°F / > 370°C Not Applicable > 75 cps at 60°F Section 10 – Stability and Reactivity Product is stable under typical use temperatures. Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.		1)					
Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature; and Viscosity Not Applicable -75 cps at 60°F Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.		1)	1 12				
Auto-ignition temperature Decomposition temperature; and Viscosity Not Applicable ~75 cps at 60°F Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.							
Decomposition temperature; and Viscosity -75 cps at 60°F Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.		er					
Viscosity ~75 cps at 60°F Section 10 – Stability and Reactivity Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.							
Section 10 – Stability and ReactivityReactivityProduct is stable under typical use temperatures.Chemical StabilityProduct is stable under typical use temperatures.Hazardous ReactionsAvoid contact with oxidizing materials and strong acids.Conditions to AvoidHeat, flames, ignition sources and incompatibles.							
Reactivity Product is stable under typical use temperatures. Chemical Stability Product is stable under typical use temperatures. Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.	VISCUSILY	Continu					
Chemical StabilityProduct is stable under typical use temperatures.Hazardous ReactionsAvoid contact with oxidizing materials and strong acids.Conditions to AvoidHeat, flames, ignition sources and incompatibles.	Doodivity						
Hazardous Reactions Avoid contact with oxidizing materials and strong acids. Conditions to Avoid Heat, flames, ignition sources and incompatibles.			, , , , , , , , , , , , , , , , , , ,				
Conditions to Avoid Heat, flames, ignition sources and incompatibles.							
, , ,							
THE CHARLEST AND A CONTROL OF THE CO			. •				
Decomposition Products Carbon dioxide and carbon monoxide may form when heated to decomposition.							

		Alde	hydes, alcohols or ot	her organic a	cids m	nay a	lso be formed.		
			ction 11 - Toxico						
Likely Routes of Exp	osure			s / Skin / Inge					
	Effects f	rom Sho	Effects from Long Term Exposure						
Delayed Effects	Irritation of								
	Irritation of								
Chronic Effects Not Applicable				Lactic acido following ch			and seizures have been tion.	reported	
The numerical meas	sures of to	cicity (e.g.	, acute toxicity				absorption in rabbits is	>10,000	
estimates such as the estimated amount [contest animals in a single]	of a substa			mg/kg Inge	estion:	The	oral LD 50 for rats is 20,	000 mg/kg	
Description of the sy symptoms associate including symptoms exposure.	he chemical	Irritation of affected areas. Lactic acidosis, stupor and seizures.							
Listed in the Nationa	ıl.		Found to be a pote				Found to be a		
Toxicology Program Report on Carcinoge	(NTP)	No	carcinogen in the International Agency for Research on		potential carcinogen by OSHA	No			
11 11 11 13			Cancer (IARC) Mor			•			
Fastanisk			ection 12 – Ecol	ogicai info	rmat	ion			
Ecotoxicity	Low E	cotoxicity							
Persistence and Degradability		gradable							
Bioaccumulation			umulate significantly	9 - 20 - 20 1			1 1		
Mobility in Soil	water	Dissolves in water. If product enters soil, it will be highly mobile and may contaminate ground water							
Other Adverse Effects	No Da	No Data Available							
		Se	ction 13 - Dispo	sal Consid	lerati	ons			
				ter. Contact lo	ocal se	ewer,	municipal, state and/or	federal	
agencies to determine	ne appropi								
			ection 14 - Tran	sport Infor	rmati	on			
Is product DOT regu	lated in No	on-Bulk pa	<u> </u>				No		
			DOT	BULK					
UN number		Not Regulated							
UN proper shipping	name			Not Regulated					
Transport hazard cla		Not Regulated							
	Packing group number						Not Regulated		
	, .	•	is a marine pollutant Code (IMDG Code)	•	the		Not Regulated		
International Code for	or the Con	struction a	g to Annex II of MARI and Equipment of Shi emical Code (IBC Co	ps Carrying D			Not Regulated		
Any special precauti with, in connection v	of or needs t		ply	Not Regulated					
premises	15 Da	alete	/Information /N	at indicate	d c 16-	n L	ore also on this CD	C)	
Section	15 – Ke						ere else on this SD		
Safety Regulations acceptable. OSHA "Hazardous Chemic			cceptable. OSHA Haz lazardous Chemical" andard, 29 CFR 191						
Health Regulations NSF. Components con				ed as Generally Regarded as Safe (GRAS) by the FDA and form to requirements of 21 CFR 184.1666; 21 CFR 1705, 74.1706, 74.2340 as applicable.					
Environmental Regu	lations		SDA certified biobase			_			
SARA 311/312 Based upon available i material is classified as			nformation, th	nis		erfund Amendments and uthorization Act of 1986 Title III			

	healt	h and/or physical hazards	(SARA) Sections 311 and 312:		
	according to Section 311 & 312		Immediate (Acute) Health Hazard - No;		
		-	Delayed (Chronic) Health Hazard - No;		
			Fire Hazard - No; Reactive Hazard - No; Sudden Release of Pressure Hazard - No. Section 313: To the best of our knowledge, this product does not contain chemicals at levels which		
			require reporting		
			under this statute.		
	Blue/Health		0		
HMIS	Red/	Flammability	1		
TIIVIIS	Oran	ge/Physical Hazard	0		
	White	e/Personal Protection	X		
	Health (Blue)		0		
NFPA	Flammability (Red)		1		
0(no hazard) to 4(severe risk)	Special (White)		0		
	Instability/Reactivity (Yellow)		N/A		
US Toxic Substance Control Act		All components of this product are on the TSCA Inventory or are exemp			
		from TSCA Inventory requirements under 40 CFR 720.30			
CEPA – Domestic Substances List (DSL)		All substances contained in this product are listed on the Canadian Domestic			
		Substances List (DSL) or are not required to be listed.			
	_	4' 40 O(I I (4'			

Section 16 – Other Information

This SDS is applicable for all dilutions and containers for this brand of product. The information herein is provided in good faith and believed to be accurate as of the effective revision date shown. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/ user's responsibility to ensure that activities comply with all federal, state, provincial or local law.

Product Dilutions Differentials								
Properties ¹	60%	50%	40%	35%	30%	25%		
SAFE-T-THERM® GRAS Biobased	60%	50%	40%	35%	30%	25%		
Performance Additives and Water	40%	50%	60%	65%	70%	75%		
Specific Gravity (15/15°C 60/60°F)	1.050 - 1.059	1.043 - 1.054	1.035 - 1.042	1.034 - 1.042	1.029 - 1.038	1.024 - 1.034		
Reserve Alkalinity (min)	6	6	4	4	3	3		
Freeze Point Max	-49°F / -45°C	-22°F / -31°C	-4°F / -20°C	4°F / -16°C	10°F / -12°C	15°F / -10°C		