

 HOUGHTON	TYPE OF RAW MATERIAL							CORROSION PACKAGE					APPLICATION						PHYSICAL
	Color	Propylene USP Grade	Propylene Industrial Grade	Ethylene	Ethyl Alcohol	1,3 Propanediol	Renewable Source	Generally Recognized As Safe	Standard	Enhanced	Aluminum safe	Nitrite based	Incidental food contact may occur	Incidental food contact may not occur	Aluminum based systems	Stationary engines	Data centers	Geothermal	Temperature Range
SAFE-T-THERM® GRAS		✓						✓	✓				✓					✓	-50° to 230° F
SAFE-T-THERM® HD			✓							✓				✓				✓	-50° to 325° F
SAFE-T-THERM® HDN			✓							✓		✓		✓					-50° to 325° F
SAFE-T-THERM® LC 25		✓								✓				✓			✓	✓	-50° to 230° F
SAFE-T-THERM® AL			✓								✓			✓	✓			✓	-50° to 225° F
SAFE-T-THERM® GV			✓					✓						✓					-50° to 225° F
SAFE-T-THERM® GRAS Biobased		✓					✓	✓	✓				✓						-50° to 230° F
SAFE-T-THERM® HD Biobased							✓			✓				✓					-50° to 325° F
SAFE-T-THERM® PDO						✓	✓			✓				✓					-50° to 300° F
WINTREX®				✓					✓					✓					-60° to 220° F
WINTREX® HD				✓						✓				✓					-60° to 350° F
WINTREX® N				✓						✓		✓		✓		✓			-60° to 220° F
GeoSafe®					✓				✓					✓				✓	

Call us today for more information (800)777-2466

www.houghton.com

All available in drums, totes & bulk in various concentrations