HOUGHTON

	Color	TYPE OF RAW MATERIAL						CORROSION PACKAGE					APPLICATION						PHYSICAL
		Propylene USP Grade	Propylene Industrial Grade	Ethylene	Ethyl Alcohol	1,3 Propanediol	Renewable Source	Generally Recognized As Safe	Standard	Enhanced	Aluminum safe	Nitrite based	Incidental food contact may occur	Incidental food contact may not occur	Aluminum based systems	Stationary engines	Data centers	Geothermal	Temperature Range
SAFE-T-THERM® GRAS		✓						✓	✓				✓					✓	-50° to 230° F
SAFE-T-THERM® HD			✓							✓				✓				✓	-50° to 325° F
SAFE-T-THERM® HDN			✓							✓		✓		✓					-50° to 325° F
SAFE-T-THERM® LC 25		✓								✓				✓			✓	✓	-50° to 230° F
SAFE-T-THERM® AL			✓								✓			✓	✓			✓	-50° to 225° F
SAFE-T-THERM® GV			✓						✓					✓					-50° to 225° F
SAFE-T-THERM® GRAS Biobased		✓					✓	✓	✓				✓						-50° to 230° F
SAFE-T-THERM® HD Biobased							✓			✓				✓					-50° to 325° F
SAFE-T-THERM® PDO						✓	✓			✓				✓					-50° to 300° F
WINTREX®				✓					✓					✓					-60° to 220° F
WINTREX® HD				✓						✓				✓					-60° to 350° F
WINTREX® N				✓						✓		✓		✓		✓			-60° to 220° F
CRYPTOCOOL®				✓					✓					✓			✓		-60° to 220° F
GeoSafe®					✓				✓					✓				✓	

Call us today for more information (800)777-2466

www.houghton.com

Available in pails, drums, totes & bulk in various concentrations